

E.Miroglio
EAD Cert.N°
SOF0170206
ISO 9001:2008SAFE &
healthy
working
conditionsNO harmful
or irritant
chemicals
used**impiego**

macchina rettilinea su finezza 12 a 1 filo, 7 a 2 fili.
Per valutare i cali nei vari punti maglia, é necessario esegui-
re un capo prototipo e sottoporlo a test di lavaggio.
In fase di smacchinatura, porre particolare attenzione alla
messa a punto della macchina, per limitare le rotture della
piattina di poliestere.

scarto di lavorazione

la particolare costruzione di quest'articolo e il processo di
tintura comportano uno scarto del 5-7%.

colori

uniti

solidità

secondo le norme UNI/ISO; per i rigati con colori contra-
stanti, è necessario richiedere solidità specifiche ed esegui-
re test di lavaggio.

finissaggio industriale

vaporizzare abbondantemente in fase di stiro; per una
mano più fluida e per eliminare le tensioni di smacchinatu-
ra, si consiglia un lavaggio con ammorbidente specifico.

servizio campionature fino al 31-12-2018

* colori pronti per campionatura

*per informazioni sull'utilizzo dell'articolo e dei bagni
ottimali di tintura, vi preghiamo di richiedere la s
cheda tecnica.*

use

*flat-knitting machine gauge 12 for 1-ply, 7 for 2-ply.
Make and wash a prototype garment to evaluate
shrinkage in the different knits.
Pay great attention during knitting to the set-up of the
machine, in order to limit the polyester breakage.*

knitting waste

*the particular yarn construction and dyeing process may
cause a 5-7% knitting waste.*

colours

solid

fastness

*in compliance with UNI/ISO norms; for striped garments
with contrasting colours, it is recommended to ask for spe-
cific fastness and carry out washing tests.*

industrial finishing

*steam generously during ironing; for a smoother hand and
to eliminate the shrinkage due to the knitting tensions, it is
suggested to wash with specific softener.*

sampling service until 31-12-2018

* colours ready for sampling

*for any information regarding the use and dye-lot
sizes of the yarn please ask for the technical sheet.*

