

E.MIROGLIO EAD

Kv. Industrialen 8800 Sliven - BULGARIA
Tel (00359 44) 612423
Fax (00359 44) 612260 / 612274
e-mail: mirogl.io.lana@emirogl.io.com

1 ARTICLE 87633 STAM
1 LINE LANA-WORSTED
1 TEXTILE - YARN DYED

28/08/2013

1 CONSTRUCTION CHARACTERISTICS

MATERIAL COMPOSITION ISO 1833/5088 064 POLYESTER DISC.
035 VISCOSE
001 ELASTANE

CONSTRUCTION TWILL

WEIGHT G/MQ-G/ML ISO 3801 228 330

TOT WIDTH MIN/MAX CM ISO 22198 143 145

WORKING WIDTH MIN/MAX CM ISO 22198 140 : 142

COUNT ENDS TEX 14,75X2;DTEX 112

COUNT PICKS TEX 30,8 (NE40/2+3,3EL)

THREADS WARP - WEFT N/CM ISO 1049-2 35,7 : 27,5

1 FINISH CHARACTERISTICS

DYESTUFFS DISPERSION-REACTIVE DYES
FINISHING SOFTENER

1 CARE LABELLING



1 MECHANICAL PROPERTIES

STRENGTH WARP / WEFT N ISO 13934-1 850 : 600

SLIDING SEAM WAR/WEF WEF/WAR 5MM KG ISO 13936-1 18,0 : 18,0

TENDENCY TO PILLING MARTINDALE (2000) ISO 12945-2 2-3

SEWING INSTR.NEEDLE SES N. STICH CM. 70 : 3-4

1 DIMENSIONAL STABILITY

SHRINKAGE HOFFMANN DIN 53894-T2 WARP% WEFT%
-3,0 : -3,0

SHRINKAGE WASCATOR 40 C ISO 6330 -2,0 : -2,0

1 COLOUR FASTNESS

WASHING 40°C ISO 105C06 AS2 LIGHT DARK
4 : 3-4

PERSPIRATION ACID ISO 105E04 4 : 3-4

PERSPIRATION ALKALINE ISO 105E04 4 : 3-4

WATER 4 HOURS ISO 105E01 4 : 3-4

RUBBING WET ISO 105X12 4 : 3

RUBBING DRY ISO 105X12 4 : 3

1 TRADE SPECIFIC INFORMATION

CUSTOM CODE 55151190000

OEKO-TEX CERTIFICATE RDP 001772.0

NOTES