

E.MIROGLIO EAD

Kv. Industrialen 8800 Sliven - BULGARIA
Tel (00359 44) 612423
Fax (00359 44) 612260 / 612274
e-mail: mirogl.io.lana@emirogl.io.com

1 ARTICLE 89028 SITO
1 LINE LANA-WORSTED
1 TEXTILE - YARN DYED

28/08/2013

1 CONSTRUCTION CHARACTERISTICS

MATERIAL COMPOSITION ISO 1833/5088 063 POLYESTER DISC.
035 VISCOSE
002 ELASTANE
CONSTRUCTION PLAIN WEAVE 1/1
WEIGHT G/MQ-G/ML ISO 3801 138 200
TOT WIDTH MIN/MAX CM ISO 22198 143 145
WORKING WIDTH MIN/MAX CM ISO 22198 140 : 142
COUNT ENDS TEX 14,75X1
COUNT PICKS TEX 19,66+EL
THREADS WARP - WEFT N/CM ISO 1049-2 40,2 : 27,2

1 FINISH CHARACTERISTICS

DYESTUFFS DISPERSION-REACTIVE DYES
FINISHING SOFTENER

1 CARE LABELLING



1 MECHANICAL PROPERTIES

STRENGTH WARP / WEFT N ISO 13934-1 450 : 300
SLIDING SEAM WAR/WEF WEF/WAR 5MM KG ISO 13936-1 15,0 : 20,0
TENDENCY TO PILLING MARTINDALE (2000) ISO 12945-2 2-3
SEWING INSTR.NEEDLE SES N. STICH CM. 70___ : 3-4

1 DIMENSIONAL STABILITY

SHRINKAGE HOFFMANN DIN 53894-T2 WARP% WEFT%
-3,0 : -3,0
SHRINKAGE WASCATOR 40 C ISO 6330 -3,0 : -3,0

1 COLOUR FASTNESS

WASHING 40°C ISO 105C06 AS2 LIGHT DARK
4 : 3-4
PERSPIRATION ACID ISO 105E04 4 : 3-4
PERSPIRATION ALKALINE ISO 105E04 4 : 3-4
WATER 4 HOURS ISO 105E01 4 : 3-4
RUBBING WET ISO 105X12 4 : 3
RUBBING DRY ISO 105X12 4 : 3

1 TRADE SPECIFIC INFORMATION

CUSTOM CODE 55151399000
OEKO-TEX CERTIFICATE RDP 001772.0

NOTES