

E.Miroglio EAD ISO 14001:2015 Cert. N° BG.121922E/U ISO 9001:2015 Cert. N° BG.121922Q/U



healthy working conditions



NO harmful or irritant chemicals used

impiego

macchina rettilinea su finezza 16-18 ad 1 filo, 14 a 1 filo, 12 a 2 fili, circolare da 16 a 20 ad 1 filo, cotton 24-27-30

Per valutare i cali nei vari punti maglia, è necessario eseguire un capo prototipo e sottoporlo a test di lavaggio

scarto di lavorazione

la particolare costruzione di questo articolo e il processo di tintura comportano uno scarto del 5-7%.

colori

uniti

solidità

secondo le norme UNI/ISO; per i rigati con colori contrastanti, è necessario richiedere solidità specifiche ed eseguire test di lavaggio.

finissaggio industriale

vaporizzare abbondantemente in fase di stiro; per una mano più fluida e per eliminare le tensioni di smacchinatura, si consiglia un lavaggio con ammorbidente specifico.

servizio campionature fino al 30-06-2023

* colori pronti per campionatura

per informazioni sull'utilizzo dell'articolo e dei bagni ottimali di tintura, vi preghiamo di richiedere la scheda tecnica.

use

flat-knitting machine gauge 16-18 for 1-ply, 14 for 1, gauge 12 for 2 ply, circular from 16 to 20 for 1-ply, cotton 24-27-30 gauge for 1-ply.

Make and wash a prototype garment to evaluate shrinkage in the different knits.

knitting waste

the particular yarn construction and dyeing process cause a 5-7% knitting waste.

colours

solid

fastness

in compliance with UNI/ISO norms; for striped garments with contrasting colours, it is recommended to ask for specific fastness and carry out washing tests.

industrial finishing

steam generously during ironing; for a smoother hand and to eliminate the shrinkage due to the knitting tensions, it is suggested to wash with specific softener.

sampling service until 30-06-2023

* colours ready for sampling

for any information regarding the use and dye-lot sizes of the yarn please ask for the technical sheet.

•1 bianco white •2 chiari light •3 medi medium •4 scuri dark •5 special special















